



designed for scientists



IKA PEN 10 - 200 µl, Electronic Pipette

/// Data Sheet

The IKA PEN is the first of its kind electronic pipette which is engineered with an innovative ultra-slim design that delivers the performance of an electronic pipette in a lighter, more balanced form.

The streamlined body fits naturally in the hand, improving control and comfort during extended pipetting sessions. A user-friendly interface allows quick adjustments, while five pipetting modes provide flexibility for a wide range of laboratory applications and simplifies complex pipetting protocols, saving time and increasing lab productivity.

Designed for modern labs, the pipette also features wireless connectivity and a free App for convenient parameter



designed for scientists

setting and wireless control to streamline workflows. It also comes with USB-C charging and a rechargeable lithium battery for reliable, all-day performance.

Key Features

- > Innovative ultra-slim, lightweight design
- > Better balance and ergonomics than traditional bulky electronic pipettes
- > User-friendly interface for easy operation
- > Wireless connectivity for smart integration
- > USB-C charging with rechargeable lithium battery
- > Five pipetting modes (Pipette, Reverse Pipetting, Multi Dispensing, Dilute, Manual Measurement) for versatile applications



designed for scientists

Technical Data

Design	Air displacement piston-operated pipette
Handling	electronic
Volume	variable
Number of channels	1
Nominal volume [μl]	200
Volume min. [μl]	10
Volume max. [μl]	200
Increments [μl]	0.1
Accuracy with nominal volume [μl]	±1.2
Accuracy with nominal volume [%]	±0.6
Precision with nominal volume [μl]	±0.4
Precision with nominal volume [%]	±0.2
Accuracy with 50% of nominal volume [μl]	±1
Accuracy with 50% of nominal volume [%]	±1
Precision with 50% of nominal volume [μl]	±0.3
Precision with 50% of nominal volume [%]	±0.3
Accuracy with 10% of nominal volume [μl]	±0.5
Accuracy with 10% of nominal volume [%]	±2.5
Precision with 10% of nominal volume [μl]	±0.14
Precision with 10% of nominal volume [%]	±0.7
Certificate of conformity according to ISO 8655	yes
Autoclavable	partially
Piston material	stainless steel DLC coated
Charging time [h]	3
Working time [h]	8
Battery type	Rechargeable lithium ion 10440 (Convex type)
Battery capacity [mAh]	350
Dimensions (W x H x D) [mm]	15.5 x 204.3 x 28.2
Weight [kg]	0.078
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
DC Voltage [V=]	3.7
Batteries included with the product?	yes
Number of Batteries	1
How is the Battery packaged	within appliance
Battery Voltage [V]	3.7